



US006427421B1

(12) **United States Patent**
Belmont et al.

(10) **Patent No.:** **US 6,427,421 B1**
(45) **Date of Patent:** ***Aug. 6, 2002**

(54) **METHOD OF MANUFACTURING
RECLOSEABLE PACKAGES**

(75) **Inventors:** **Kirk E. Belmont, Fairport; Ian J.
Barclay, Marion, both of NY (US)**

(73) **Assignee:** **Pactiv Corporation, Lake Forest, IL
(US)**

(*) **Notice:** Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

This patent is subject to a terminal dis-
claimer.

3,868,891 A	3/1975	Parish	93/8 W
3,948,705 A	4/1976	Ausnit	156/73.4
4,094,729 A	6/1978	Boccia	156/515
4,101,355 A	7/1978	Ausnit	156/66
4,196,030 A	4/1980	Ausnit	156/91
4,232,429 A	11/1980	Friedberg	24/205.11 R
4,240,241 A	12/1980	Sanborn, Jr.	53/142
4,277,241 A	7/1981	Schulze	493/196
4,341,575 A	7/1982	Herz	156/66
4,355,494 A	10/1982	Tilman	53/416
4,372,793 A	2/1983	Herz	156/66
4,415,386 A	11/1983	Ferrell et al.	156/64
RE31,487 E	1/1984	Friedberg	24/386
4,430,070 A	2/1984	Ausnit	493/215
4,437,293 A	3/1984	Sanborn, Jr.	53/412

(List continued on next page.)

(21) **Appl. No.:** **09/627,728**

(22) **Filed:** **Jul. 28, 2000**

Related U.S. Application Data

(62) **Division of application No. 09/307,843, filed on May 10,
1999, now Pat. No. 6,327,754.**

(51) **Int. Cl.⁷** **B65B 9/06; B65B 61/18**

(52) **U.S. Cl.** **53/412; 53/450**

(58) **Field of Search** **53/412, 450, 133.4,
53/139.2, 550; 493/213, 214, 927**

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,259,951 A	7/1966	Zimmerman	24/201
3,381,592 A	5/1968	Ravel	93/8
3,426,396 A	2/1969	Laguerre	24/201
3,473,589 A	10/1969	Götz	150/3
3,532,571 A	10/1970	Ausnit	156/91
RE27,174 E	9/1971	Ausnit	150/3
3,608,439 A	9/1971	Ausnit	93/35 R
3,613,524 A	10/1971	Behr et al.	93/33 R
3,701,191 A	10/1972	Laguerre	29/207.5 SL
3,701,192 A	10/1972	Laguerre	29/207.5 SL
3,785,111 A	1/1974	Pike	53/14
3,790,992 A	2/1974	Herz	24/201 C
3,839,128 A	10/1974	Arai	156/583

FOREIGN PATENT DOCUMENTS

EP	0 978 450 A1	9/2000	B65B/9/20
FR	1564039	10/1969	
GB	2085519 A	4/1982	A44B/19/62
WO	WO 99/24325	5/1999	B65B/61/18

OTHER PUBLICATIONS

PCT Search Report for International Appl. No. PCT/US00/
12302 dated Aug. 28, 2000.


Primary Examiner—John Sipos

(74) *Attorney, Agent, or Firm*—Jenkins & Gilchrist

(57) **ABSTRACT**

A plurality of fastener arrangements for use in manufactur-
ing recloseable bags comprising a first fastener and a second
fastener connected to the first fastener. Each of said fasteners
comprising a male track with a male profile, a female track
with a female profile and a slider. The male and female
profiles are releasably engageable to each other. The slider
is slidably mounted to the fastener for movement between a
closed position and an open position. The male and female
profiles are engaged to each other while the slider is in the
closed position. The male and female profiles are disengaged
from each other in response to movement of the slider from
the closed position to the open position.

37 Claims, 6 Drawing Sheets



U.S. PATENT DOCUMENTS

4,446,088 A	5/1984	Daines	264/155	5,116,301 A	5/1992	Robinson et al.	493/215
4,517,788 A	5/1985	Scheffers	53/459	5,127,208 A	7/1992	Custer et al.	53/412
4,528,224 A	7/1985	Ausnit	428/36	5,131,121 A	7/1992	Herrington, Jr. et al.	24/436
4,563,319 A	1/1986	Ausnit et al.	264/146	5,147,272 A	9/1992	Richison et al.	493/195
4,581,006 A	4/1986	Hugues et al.	493/213	5,161,286 A	11/1992	Herrington, Jr. et al.	24/387
4,582,549 A	4/1986	Ferrell	156/66	5,167,608 A	12/1992	Steffens, Jr. et al.	493/214
4,601,694 A	7/1986	Ausnit	493/381	5,179,816 A	1/1993	Wojnicki	53/133.4
4,612,153 A	9/1986	Mangla	264/154	5,188,461 A	2/1993	Sorensen	383/63
4,617,683 A	10/1986	Christoff	383/63	5,198,055 A	3/1993	Wirth et al.	156/66
4,620,320 A	10/1986	Sullivan	383/79	5,211,482 A	5/1993	Tilman	383/202
4,651,504 A	3/1987	Bentsen	53/452	5,247,781 A	9/1993	Runge	53/412
4,652,496 A	3/1987	Yasufuku et al.	428/425.9	5,254,073 A	10/1993	Richison et al.	493/195
4,655,862 A	4/1987	Christoff et al.	156/66	5,259,904 A	11/1993	Ausnit	156/244.15
4,663,915 A	5/1987	Van Erden et al.	53/450	5,273,511 A	12/1993	Boeckman	493/195
4,666,536 A	5/1987	Van Erden et al.	156/64	RE34,554 E	3/1994	Ausnit	383/63
4,673,383 A	6/1987	Bentsen	493/381	5,322,579 A	6/1994	Van Erden	156/66
4,691,372 A	9/1987	Van Erden	383/63	5,334,127 A	8/1994	Bruno et al.	493/194
4,703,518 A	10/1987	Ausnit	383/63	5,383,989 A	1/1995	McMahon	156/66
4,709,398 A	11/1987	Ausnit	383/63	5,391,136 A	2/1995	Makowka	493/210
4,709,533 A	12/1987	Ausnit	53/451	5,400,565 A	3/1995	Terminella et al.	53/133.4
4,710,157 A	12/1987	Posey	493/213	5,400,568 A	3/1995	Kanemitsu et al.	53/412
4,782,951 A	11/1988	Griesbach et al.	206/484	RE34,905 E	4/1995	Ausnit	53/412
4,786,190 A	11/1988	Van Erden et al.	383/61	RE34,906 E	4/1995	Tamaki et al.	123/399
4,787,880 A	11/1988	Ausnit	493/213	5,403,094 A	4/1995	Tomic	383/63
4,790,126 A	12/1988	Boeckmann	53/451	5,405,478 A	4/1995	Richardson et al.	156/308.4
4,792,240 A	12/1988	Ausnit	383/63	5,405,629 A	4/1995	Marnocha et al.	426/122
4,807,300 A	2/1989	Ausnit et al.	383/65	5,412,924 A	5/1995	Ausnit	53/412
4,812,074 A	3/1989	Ausnit et al.	493/213	5,415,904 A	5/1995	Takubo et al.	428/35.2
4,832,505 A	5/1989	Ausnit et al.	383/5	5,425,216 A	6/1995	Ausnit	53/410
4,840,012 A	6/1989	Boeckmann	53/410	5,425,825 A	6/1995	Rasko et al.	156/66
4,840,611 A	6/1989	Van Erden et al.	493/213	5,431,760 A	7/1995	Donovan	156/66
4,844,759 A	7/1989	Boeckmann	156/66	5,435,864 A	7/1995	Machacek et al.	156/66
4,850,178 A	7/1989	Ausnit	53/570	5,442,837 A	8/1995	Morgan	24/400
4,863,285 A	9/1989	Claxton	383/37	5,442,838 A	8/1995	Richardson et al.	24/402
4,876,842 A	10/1989	Ausnit	53/410	5,448,807 A	9/1995	Herrington, Jr.	24/399
4,878,987 A	11/1989	Van Erden	156/519	5,456,928 A	10/1995	Hustad et al.	426/87
4,892,414 A	1/1990	Ausnit	383/63	5,461,845 A	10/1995	Yeager	53/451
4,892,512 A	1/1990	Branson	493/194	5,470,156 A	11/1995	May	383/210
4,894,975 A	1/1990	Ausnit	53/412	5,482,375 A	1/1996	Richardson et al.	383/64
4,909,017 A	3/1990	McMahon et al.	53/410	5,486,051 A	1/1996	May	383/200
4,924,655 A	5/1990	Posey	53/128	5,489,252 A	2/1996	May	383/210
4,925,316 A	5/1990	Van Erden et al.	383/61	5,492,411 A	2/1996	May	383/5
4,925,318 A	5/1990	Sorensen	383/63	5,505,037 A	4/1996	Terminella et al.	53/133.4
4,929,225 A	5/1990	Ausnit et al.	493/213	5,509,735 A	4/1996	May	383/210
4,941,307 A	7/1990	Wojcik	53/412	5,511,884 A	4/1996	Bruno et al.	383/63
4,969,309 A	11/1990	Schwarz et al.	53/412	5,513,915 A	5/1996	May	383/210
4,971,454 A	11/1990	Branson et al.	383/61	5,519,982 A	5/1996	Herber et al.	53/412
4,974,395 A	12/1990	McMahon	53/551	5,525,363 A	6/1996	Herber et al.	426/130
4,993,212 A	2/1991	Veoukas	53/451	5,542,902 A	8/1996	Richison et al.	493/195
5,005,707 A	4/1991	Hustad et al.	206/632	5,551,127 A	9/1996	May	24/30.5 R
5,010,627 A	4/1991	Herrington et al.	24/400	5,551,208 A	9/1996	Van Erden	53/139.2
5,014,498 A	5/1991	McMahon	53/451	5,552,202 A	9/1996	May	428/43
5,024,537 A	6/1991	Tilman	383/63	5,557,907 A	9/1996	Malin et al.	53/139.2
5,027,584 A	7/1991	McMahon et al.	53/451	5,558,613 A	9/1996	Tilman et al.	493/214
5,036,643 A	8/1991	Bodolay	53/128.1	5,561,966 A	10/1996	English	53/412
5,042,224 A	8/1991	McMahon	53/133.4	5,564,259 A	10/1996	Stolmeier	53/410
5,046,300 A	9/1991	Custer et al.	53/412	5,573,614 A	11/1996	Tilman et al.	156/66
5,063,639 A	11/1991	Boeckmann et al.	24/30.5 R	5,582,853 A	12/1996	Marnocha et al.	426/122
5,063,644 A	11/1991	Herrington et al.	24/400	5,592,802 A	1/1997	Malin et al.	53/133.4
5,067,208 A	11/1991	Herrington, Jr. et al.	24/400	5,613,934 A	3/1997	May	493/214
5,067,822 A	11/1991	Wirth et al.	383/61	5,622,431 A	4/1997	Simonsen	383/63
5,071,689 A	12/1991	Tilman	428/121	5,628,566 A	5/1997	Schreiter	383/63
5,072,571 A	12/1991	Boeckmann	53/133.4	5,647,671 A	7/1997	May	383/210
5,085,031 A	2/1992	McDonald	53/412	5,664,296 A	9/1997	May	24/30.5 R
5,088,971 A	2/1992	Herrington	493/203	5,669,715 A	9/1997	Dobreski et al.	383/5
5,092,831 A	3/1992	James et al.	493/394	5,682,730 A	11/1997	Dobreski	53/469
5,096,516 A	3/1992	McDonald et al.	156/66	5,711,751 A	1/1998	Harmanoglu	493/224
5,105,603 A	4/1992	Natterer	53/412	5,713,669 A	2/1998	Thomas et al.	383/204
5,107,658 A	4/1992	Hustad et al.	53/408	5,725,312 A	3/1998	May	383/210
5,111,643 A	5/1992	Hobock	53/551	5,782,733 A	7/1998	Yeager	493/213
				5,823,933 A	10/1998	Yeager	493/213

US 6,427,421 B1

Page 3

5,833,791 A	11/1998	Bryniarski et al.	156/244.25	5,956,924 A	9/1999	Thieman	53/412
5,851,070 A	12/1998	Dobreski et al.	383/63	6,138,436 A	10/2000	Malin et al.	
5,896,627 A	4/1999	Cappel et al.	24/400	6,138,439 A *	10/2000	McMahon et al.	53/412
5,906,438 A	5/1999	Laudenberg	383/63	6,148,588 A *	11/2000	Thomas et al.	53/133.4
5,924,173 A	7/1999	Dobreski et al.	24/400	6,279,298 B1 *	8/2001	Thomas et al.	53/133.4
5,938,337 A	8/1999	Provan et al.	383/5				
5,953,796 A	9/1999	McMahon et al.	24/400				
5,956,815 A	9/1999	O'Connor et al.	24/30.5				

* cited by examiner

Fig. 1





Fig. 2






Fig. 3a




Fig. 3b




Fig. 3c




Fig. 3d






Fig. 5*Fig. 6*




Fig. 8a




Fig. 8b






Fig. 9*Fig. 10*

METHOD OF MANUFACTURING RECLOSEABLE PACKAGES

RELATED APPLICATIONS

This application is a divisional of U.S. patent application Ser. No. 09/307,843, filed May 10, 1999 now U.S. Pat. No. 6,327,754.

This application is related to an application entitled "Assembly and Accumulation of Sliders for Profiled Zippers" Ser. No. 09/307,893; and to an application entitled "Zipper and Zipper Arrangements and Methods of Manufacturing the Same" Ser. No. 09/307,937. Both applications were filed concurrently with U.S. Ser. No. 09/307,843, and are assigned to the same assignee as the assignee of this application. Both applications and their disclosures are incorporated herein in their entirety.

FIELD OF THE INVENTION

The present invention relates generally to the packaging industry. More particularly, the invention relates to a fastener with a slider for use in a recloseable package.

BACKGROUND OF THE INVENTION

Plastic packages are popular for storing food products and other items. Recloseable packages that can be securely closed and reopened are particularly popular due to their ability to maintain freshness of the food stored in the package and/or to minimize leakage into and out of the package. Thus, recloseable packages are very common, especially in the food industry. Recloseable packages are typically made to be recloseable via the use of a recloseable feature such as a resealable adhesive seal or a recloseable zipper. Recloseable zippers can be opened and closed either by pressure or by the use of an auxiliary slider mechanism. These packages are used one at a time by consumers and large numbers of these packages are also used by businesses to package items that are then sold to consumers. An example of a business that uses a large number of these packages is a food producer and packer. For example, nuts, candy, snacks, salt, cheese, other food and non-food products can be packed in these packages by form, fill and seal machines and sold to consumers.

For a variety of reasons, including difficulty in closing the zipper, some consumers prefer an easier way to open and close the zippers on these packages. As a result, zipper packages with the slider to open and close the zipper have become popular with consumers. Product manufacturers, however, have rarely used the zipper with slider in their form, fill and seal machines because there has not been a way to assemble and accumulate the zippers with sliders in a configuration that can be easily and quickly fed to the form, fill and seal machines. A need therefore exists for an efficient method and apparatus for providing products within a recloseable package. Additionally, a need exists for a fastener with slider thereon that can easily and efficiently be used in the manufacture of recloseable bags.

SUMMARY OF THE INVENTION

In one aspect of the present invention, there is provided a fastener arrangement for use in manufacturing recloseable bags. The fastener arrangement comprises a first fastener connected to a second fastener. Each of the fasteners comprise a male track with a male profile, a female track with a female profile and a slider. The male and female profiles are releasably engageable to each other. The slider is slidably

mounted to the fastener for movement between a closed position and an open position. The male and female profiles are engaged to each other while the slider is in the closed position. The male and female profiles are disengaged from each other in response to movement of said slider from the closed position to the open position. The first fastener may be connected in line with the second fastener. Additionally, the first fastener may be connected to the second fastener such that the male and female tracks of the first fastener are substantially parallel to the male and female tracks of the second fastener.

In another aspect of the present invention, there is provided a sheet of zippers for use in manufacturing recloseable packages. The sheet of zippers comprises a first zipper releasably connected to a second zipper. The first zipper and the second zipper both have a male track with a male profile, a female track with female profile and a slider. The male and female profiles are releasably engageable to each other. The slider is slidably mounted to the zipper for movement between a closed position and an open position. The male and female profiles are engaged to each other while the slider is in the closed position. The male and female profiles are disengaged from each other in response to movement of the slider from the closed position to the open position. The first zipper and second zipper may have a length approximately equal to a length of the recloseable package. The first zipper is releasably adhered to the second zipper with a releasable adhesive or with a releasable seal. The first zipper may be connected to the second zipper such that the male and female tracks of the first zipper are substantially parallel to the male and female tracks of the second zipper. Each of the zippers may further comprise a first fin extending downward from the male profile and a second fin extending downward from the female profile. The first zipper may be connected to the second zipper by releasably adhering one of the fins of the first zipper to one of the profiles of the second zipper.

In a further aspect of the present invention, there is provided a zipper arrangement for use in manufacturing recloseable bags. The zipper arrangement comprises a male track with a male profile, a female track with a female profile and a plurality of sliders. The male and female profiles are releasably engageable to each other. The plurality of sliders are slidably mounted to the engageable male and female tracks for movement between a closed position and an open position. The male and female profiles are engaged to each other while the slider is in the closed position. The male and female profiles are disengaged from each other in response to movement of said slider from said closed position to said open position. One of the sliders is positioned in a length of the male and female track corresponding to a length of one of the recloseable bags.

In a further aspect of the present invention, there is provided a method of manufacturing recloseable packages. The method comprises providing a first wall panel opposing a second wall panel, positioning a zipper with a slider between the first and second wall panels, adhering a first profile of the zipper to the first wall panel, forming a first and a second side seal in the web to define a first and a second sidewall of the package, adhering the second profile of the zipper to the second wall panel at the mouth, and cutting the side seal to separate adjacent packages. The method may further include feeding a zipper arrangement between the wall panels before positioning the zipper. The zipper arrangement comprises a continuous male track and a continuous female track with a plurality of sliders. Alternatively, the method may further include feeding a sheet of zippers

with sliders between the wall panels before positioning the zipper. The sheet of zippers comprises a plurality of zippers releasably adhered to each other. The method may further include filling the package with a product.

BRIEF DESCRIPTION OF THE DRAWINGS

Other objects and advantages of the invention will become apparent upon reading the following detailed description and upon reference to the drawings which:

FIG. 1 is a perspective view of a fastener with a slider for a recloseable bag;

FIG. 2 is a cross section of the fastener of FIG. 1;

FIG. 3a is a process diagram of a form, fill and seal process;

FIG. 3b is a cross section of another embodiment of the fastener position for the form, fill and seal process of FIG. 3a;

FIG. 3c is a cross section of another embodiment of the fastener position for the form, fill and seal process of FIG. 3a;

FIG. 3d is a cross section of another embodiment of the fastener position for the form, fill and seal process of FIG. 3a;

FIG. 4 is a perspective view of a zipper arrangement;

FIG. 5 is a roll of the zipper arrangement of FIG. 4;

FIG. 6 is a process diagram of zipper arrangement of FIG. 4 fed to the form, fill and seal process.

FIG. 7 is a process diagram for forming a sheet of fasteners;

FIG. 8a is a perspective view of a sheet of fasteners;

FIG. 8b is a cross section of two fasteners releasably adhered together of FIG. 8a;

FIG. 9 is a roll of the sheet of fasteners of FIG. 8a; and

FIG. 10 is a process diagram of the sheet of fasteners of FIG. 8a fed to the form, fill and seal process.

While the invention will be described in connection with certain preferred embodiments, it is not intended to limit the invention to the specific exemplary embodiments. On the contrary, it is intended to cover all alternatives, modifications, and equivalents as may be included within the spirit and scope of the invention as defined by the appended claims.

DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

Turning now to the drawings, FIG. 1 illustrates a mouth portion of a recloseable package 10 having a slider 12 on a fastener or zipper arrangement 14. FIG. 2 illustrates the fastener or zipper arrangement 14 of the mouth portion of the recloseable bag along line A—A. The mouth portion of the recloseable package 10 includes a pair of opposing wall panels 16 and 18 which make up a package body 20 and define a receptacle space 22. The wall panels 16 and 18 may comprise polymeric film, multilayer and multi-component laminations or coextrusions. Connected to the wall panel 16 is a male track 24 having a male profile 26 and a first fin portion 28 extending downward from the male profile 26. Connected to the other wall panel 18 is a female track 30 having a female profile 32 and a second fin portion 34 extending downward from the female profile 32. The male and female profiles 26 and 32 are releasably engageable with each other to provide a recloseable seal to the package.

In the illustrated embodiment of FIG. 2, the lower edges of the first and second fin portions 28 and 34 are joined to

each other along a one-time breakable preferential area of weakness or preferential tear area 38 to for a one-time openable tamper evident feature 40. The joined first and second fin portions 28 and 34 have a generally U-shaped or V-shaped cross-sectional configuration. The tamper evident feature 40 is described in detail in Ser. No. 08/694,093 to Thomas et al., which is incorporated herein by reference in its entirety. Other embodiments of the fastener 14 may not include the tamper evident feature leaving the fin portions 28 and 34 disconnected.

The recloseable package 10 has the slider 12 (see FIG. 1) slidably mounted to the fastener 14 for movement between a closed position and an open position. The male and female profiles 26 and 32 are engaged to each other while the slider 12 is in the closed position, and movement of the slider 12 from the closed position to the open position disengages the profiles 26 and 32 from each other (see FIG. 2). FIG. 1 depicts the open position to the left of the slider 12 and the closed position to the right of the slider 12. The composition and manner of operation of the fastener with slider arrangement is described in detail in U.S. Pat. No. 5,067,208 to Herrington, Jr. et. al., which is incorporated herein by reference in its entirety.

FIG. 3a illustrates one embodiment of a form, fill and seal process for providing a product within a recloseable package having the fastener 14 with slider 12. The process folds a web of packaging material 50, such as polymeric film, multi-layer and multi-component laminations or coextrusions consisting of polymer, paper, metalized polymer or foil in any combination. The folded web 50 forms the package body 20 and defines the receptacle space 22 bounded by the opposing wall panels 16 and 18 and a package bottom 52. The process also positions the fastener 14 with the slidably mounted slider 12 at the mouth of the recloseable package between the opposing wall panels 16 and 18. The fastener 14 with slider 12 is preferably in the closed position when fed to the form, fill and seal apparatus. As depicted in FIG. 3a, a top seal bar 56 moves back and forth to adhere the wall panel 16 to the male track 24 forming a first top seal 54. The first top seal 54 between the wall panel 16 and male track 24 is also depicted in FIG. 2. The fastener 14 may be adhered to one of the wall panels of the web 50 by heat seal, adhesive or any other appropriate method to form a strong preferably hermetic first top seal 54 (some recloseable packages require vents for air removal).

After the fastener 14 with slider 12 is attached to the wall panel 16, a vertical seal bar 58 joins the wall panels 16 and 18 together to form a side seal 60 that defines a side wall 62 of the recloseable package. The distance between adjacent side seals 60 should be approximately equal to the desired width W of the recloseable package. The side seal 60 may be formed by heat seal, adhesive or any other appropriate method to form a strong preferably hermetic seal. In the embodiment depicted, the side seal 60 is preferably formed at the notch 63 in the zipper arrangement 14 which allows easier side sealing since the vertical seal bar 58 does not have to flatten or crush the profiles 26 and 32 of the fastener 14 in order to side seal the web 50. The notch 63 will be described below. Once the sidewalls 62 of the package are defined by the side seal 60, a product 64 fills the receptacle space 22 of the package. For illustration, FIG. 3a shows a funnel 66 directing the product 64, into the package. The product 64 may be nuts, candy, snacks, salt, cheese and other food and non-food products.

After the product 64 fills the package, a second top seal bar 68 adheres the fastener 14 to the other wall panel 18 preferably hermetically sealing the product 64 within the

5

package. The second top seal bar 68 moves back and forth to provide a second top seal 70 that adheres the female track 30 to the wall panel 18. The second top seal 70 between the wall panel 18 and female track 30 is also depicted in FIG. 2. The fastener 14 may be adhered to the wall panels of the web 50 by heat seal, adhesive or any other appropriate method to form a strong preferably hermetic second top seal 70. To divide the adjacent packages of product 64 that are connected by the side seal 60, a knife 72 cuts the side seal 60 such that the side walls 60 of each package remain secure.

An end termination or stop (not shown) may be added to the ends of the fastener 14 for inhibiting or preventing the slider 16 from going past the ends of the zipper. The end terminations also hold the male and female profiles together to resist stresses applied to the profiles during normal use of the plastic bag. One type of end termination is in the form of a strap/clip that wraps over a top of a zipper. Further information concerning such an end termination may be found in U.S. Pat. No. 5,067,208, which is incorporated herein by reference in its entirety. One end of the strap is provided with a rivet-like member that penetrates through the zipper fins and into a cooperating opening at the other end of the strap. Other types of end termination are disclosed in U.S. Pat. Nos. 5,482,375, 5,448,807, 5,442,837, 5,405,478, 5,161,286, 5,131,121 and 5,088,971, which are each incorporated herein by reference in their entireties.

The form, fill and seal process may vary from the illustration of FIG. 3a and the following describes some of the possible variations. In another embodiment of the form, fill and seal process, the side seal 60 may be cut before filling the package with the product 64. In this embodiment, the process folds the web 50 and positions and top seals the fastener 14 to one of the wall panels 16. Next, the process forms and cuts the side seals 60. After the knife 72 cuts the side seals 60, the product 64 fills the package and the second top seal 70 closes the package. In another embodiment of the form, fill and seal process, the fastener may be sealed to one of the wall panels 16 prior to the folding of the web 50.

Other embodiments of the form, fill and seal process position the fastener 14 in different locations than the mouth of the web 50. FIG. 3b depicts the fastener 14 position prior to being attached to one of the wall panels 16 and 18. The fastener 14 is positioned below the mouth 74 of the web 50. In this embodiment, the recloseable package may be formed using the steps described above. Additionally in the embodiment of FIG. 3b, the fin portions 28 and 34 are not connected to provide the tamper evident feature. For the embodiment of FIG. 3b, the tamper evident feature may be provided by sealing the wall panels 16 and 18 together above the fastener 14 at the mouth 74.

FIG. 3c illustrates another alternate position for the fastener 14 adjacent the bottom 52 of the web 50. The fastener 14 has an inverted orientation compared to the orientation of the fastener in FIGS. 3a-b. More specifically, the male and female profiles are adjacent to the bottom 52 of the package with the fins extending into the body of the package. For this embodiment, the fastener 14 should be sealed to both wall panels 16 and 18 before filling the package with the product 64. For example, the process folds the web 50 and positions the fastener 14 at the bottom 52 of the web 50 and seals the fastener 14 to both of the wall panels 16 and 18. Next, the process forms and cuts the side seals 60, and the product 64 fills the package. Finally, the process seals the wall panels 16 and 18 together at the mouth 74. Alternatively, the process fills the package with the product prior to cutting the side seals 60.

FIG. 3d illustrates another alternate position for the fastener 14 and embodiment for the form, fill and seal process.

6

In this embodiment, a pair of separate webs 76 and 77 provide the wall panels 16 and 18. The process positions the fastener 14 with inverted orientation similar to FIG. 3c at the bottom of the wall panels 16 and 18 opposite the mouth 74 and seals the fastener 14 to both wall panels 16 and 18 before filling the package with the product 64. For example, the process provides a pair of webs 76 and 77 and seals the fastener 14 to both of the wall panels 16 and 18 at the bottom of the webs. Next, the process forms and cuts the side seals 60, and the product 64 fills the package. Finally, the process seals the wall panels 16 and 18 together at the mouth 74. Alternatively, the process fills the package with the product prior to cutting the side seals 60. In another embodiment of the form, fill and seal process, the fastener 14 may be sealed to one of the webs 76 prior to opposing the web 76 with the web 77.

In order to efficiently operate the form, fill and seal process described above in conjunction with FIGS. 3a-d, the fastener 14 with slider 12 should be readily fed to the form, fill and seal process. FIGS. 4-5 illustrate one embodiment for the supply of the fastener 14 with slider 12. FIG. 4 illustrates a zipper arrangement 14 with sliders 12 slidably mounted to the zipper 14 at predetermined distances d. The predetermined distance d is approximately equal to the distance between the center of the side seals 60 of the recloseable packages to insure that each package includes the slider 12. The zipper arrangement 14 comprises a continuous male track 24 having a discontinuous male profile 26 and a continuous first fin portion 28 and a continuous female track 30 having a discontinuous female profile 32 and a continuous second fin portion 34. In the embodiment depicted in FIG. 4, the first and second fin portions 28 and 34 are joined to each other along the one-time breakable preferential area of weakness 38 to provide the tamper evident feature. In another embodiment without the tamper evident feature, the first and second fin portions 28 and 34 are not joined to each other.

The zipper arrangement 14 may be formed by extruding the male track 24 and female track 30 together or separately and then joined. The sliders 12 are slidably mounted to the zipper 14 as described in detail in the patent application Ser. No. 09/307,893 entitled "Zipper and Zipper Arrangements and Methods of Manufacturing the Same" which is incorporated herein by reference in its entirety. In the embodiment illustrated in the figures, the male and female profiles of the fastener are notched 63 to allow the slider to slidably mount the fastener 14. This notching provides the discontinuous male and female profiles 26 and 32 shown in FIG. 4. The slider may be mounted onto the fastener by other means other than the embodiment illustrated in the figures. For embodiments that mount the slider without notching, the male and female profiles of FIG. 4 would be continuous.

The zipper arrangement 14 with sliders 12 at predetermined intervals may be accumulated onto a roll 80 as illustrated in FIG. 5. The roll 80 has a cylindrical core 82 around which the zipper arrangement 14 with sliders 12 is wrapped. The roll 80 may also include a pair of sidewalls 84a and 84b at the ends of the cylindrical core 82 to hold the windings of the zipper arrangement 14 on the roll 80. Alternatively, the zipper arrangement 14 may be rolled upon itself to form a cylinder. The sliders 12 may be advantageously positioned along the zipper arrangement 14 such that the roll 80 occupies a minimum amount of space. Preferably, the sliders 12 will be positioned to prevent adjacent layers of sliders from abutting or laying on top of each other.

The roll 80 of the zipper arrangement 14 with sliders 12 is particularly useful for supplying the fastener or zipper 14

with slider 12 for the form, fill and seal process described above in conjunction with FIGS. 3a-d. The zipper arrangement 14 with spaced sliders 12 simply unwinds from the roll 80 feeding into the form, fill and seal process. FIG. 6 illustrates the zipper arrangement 14 with sliders 12 being adhered to one of the wall panels 16 of the folded web 50. The unwound zipper arrangement 14 with sliders 12 is positioned at the mouth of the web 50 between the opposing wall panels 16 and 18. As depicted in FIG. 6, the first top seal bar 56 moves back and forth to attach a portion of the zipper arrangement 14 with slider 12 to the wall panel 16 to form the first top seal 54. FIG. 6 also illustrates another embodiment for the form, fill and seal process which includes another first top seal bar 86 opposite the other first top seal bar 56. The portion of the zipper arrangement 14 with slider 12 adjacent the wall panel 16 is positioned between the two first top seal bars 56 and 86 which move back and forth to sandwich the portion of the zipper with slider 12 and the wall panel 16 between the two first top seal bars 56 and 86 to adhere the portion of the zipper 14 with slider 12 to the wall panel 16.

In an alternative embodiment for the zipper arrangement, the zipper arrangement comprises a plurality of separate zipper segments connected end to end forming the zipper arrangement with sliders as depicted in FIG. 4. Each zipper includes the male track with male profile, female track with female profile, and the slider. Each zipper has a length approximately equal to the width of the recloseable package. The zippers are preferably joined together at the notch 63 by any appropriate means such as but not limited to releasably adhesives or seals and non-releasably adhesives or seals.

FIGS. 7-9 illustrate another embodiment for providing fasteners 14 with sliders 12 to the form, fill and seal process illustrated in FIGS. 3a-d. FIG. 7 illustrates a zipper arrangement 14 with sliders 12 slidably mounted at regular intervals, such as described in conjunction with FIG. 4. The intervals between the center of one slider to the center of an adjacent slider is approximately equal to the distance between the centers of adjacent side seals 60 to insure that each package includes the slider 12.

As depicted in FIG. 7, a knife 88 cuts the zipper arrangement 14 with sliders 12 into individual lengths 1. The individual lengths 1 are slightly larger than the width of the recloseable package, or in other words, substantially equal to the distance between the centers of adjacent side seals 60 to insure that each package includes the fastener. For the embodiment depicted, the notches are appropriately spaced for the knife 88 to make the cut at the notch 63.

FIG. 8a also depicts the individual lengths 1 of fasteners 14 with sliders 12 accumulated into a sheet 90. To accumulate the length of fastener 14 with slider 12, the fin 28 or 34 of one fastener 14 is releasably adhered to the profile 32 or 26 of an adjacent fastener 14 with slider 12. The fasteners are preferably positioned parallel to each other on the sheet 90. In one embodiment shown in FIG. 8b, a releasable adhesive 92 releasably adheres the adjacent fasteners 14 with sliders 12 to one another. In another embodiment, the profile 26 or 32 of one fasteners 14 with slider 12 is releasably sealed to the fin 34 or 28 of the adjacent fastener 14 with slider 12. The adjacent fasteners 14 of the sheet may be releasably adhered to each other by any appropriate means.

FIG. 9 illustrates the sheet 90 of the fasteners 14 with slider 12 wrapped into a roll 94 around a cylindrical core 96 or about itself to form a cylinder. The sheet 90 is preferably wrapped into a roll such that the parallel fasteners are

parallel to the longitudinal axis of the cylinder. Alternating the location of the slider 12 on fastener 14 optimizes the number of wrapping on the cylindrical core 96 by preventing the sliders of adjacent layers from abutting or laying on top of each other. Additionally as depicted in FIG. 8a, the location of the slider 12 on its length of zipper 14 may be alternated on the sheet 90 in order to allow multiple sheets to be stacked on top of each other such that the stacked sheets 90 occupy as small a space as possible.

The roll 94 or individual sheets 90 of lengths of zipper 14 with slider 12 is particularly useful for feeding the fastener 14 with slider 12 for the form, fill and seal process described above in conjunction with FIGS. 3a-d. The fastener 14 with slider 12 may simply unwind from the roll 94 as the sheet 90 for the form, fill and seal process. FIG. 10 illustrates the sheet 90 of fasteners 14 with sliders 12 feeding the form, fill and seal process. One individual fastener 14 with slider 12 is removed from the sheet 90 and placed either pneumatically, mechanically or electro-mechanically between the wall panels 16 and 18 at the mouth of the web 50. As shown in FIG. 10, the fastener 14 with slider 12 is positioned between the two first top seal bars 56 and 86 which move back and forth to sandwich the fastener 14 and the wall panel 16 between the two first top seal bars 56 and 86 to adhere the fastener 14 with slider 12 to the wall panel 16. This adhering of the fastener 14 with slider 12 repeats with the next fastener 14 with slider 12 detaching from the sheet 90 and being positioned at the mouth of the web 50. The next fastener 14 with slider 12 is preferably positioned immediately behind the last adhered fastener.

In another embodiment, the sheet of fasteners 90 may be formed and used in a slightly different manner than illustrated in FIGS. 7-10. In another embodiment, the knife 88 may make cuts to remove the notch 63 from the fastener 14. For this embodiment, the length of the fastener may be approximately equal to the width of the recloseable package. These fasteners may be fed to the form, fill and seal process as described above in conjunction with FIG. 10.

Although the zipper arrangement and sheet of fasteners has been described for use with the form, fill and seal process, the zipper arrangement and sheet of fasteners may be used in any recloseable packaging manufacturing process.

While the present invention has been described with reference to one or more particular embodiments, those skilled in the art will recognize that many changes may be made thereto without departing from the spirit and scope of the present invention. Each of these embodiments and obvious variations thereof is contemplated as falling within the spirit and scope of the claimed invention, which is set forth in the following claims.

What is claimed is:

1. A method of manufacturing recloseable packages, said method comprising:

providing a first wall panel opposing a second wall panel; positioning a zipper between said first and second wall panels, said zipper including a first track with a first profile and a second track with a second profile, said first and second profiles being releasably engageable to each other, and a slider slidably mounted to said zipper for movement between a closed position and an open position, said first and second profiles being engaged to each other while said slider is in said closed position, said first and second profiles being disengaged from each other in response to movement of said slider from said closed position to said open position;

9

adhering said first profile of said zipper to said first wall panel;
 forming first and second spaced side seals in said first and second wall panels to define first and second sidewalls of said package;
 adhering said second profile of said zipper to said second wall panel; and
 cutting said side seals to separate adjacent packages.

2. The method of claim 1 further including a step of feeding a zipper arrangement between said first and second wall panels before positioning said zipper, said zipper arrangement comprising a plurality of said zippers connected in line with each other.

3. The method of claim 1 further including a step of feeding a zipper sheet of said zippers to between said first and second wall panels before positioning said zipper, said sheet of zippers comprising a plurality of said zippers releasably adhered to each other.

4. The method of claim 1 wherein said zipper is positioned and said first profile of said zipper is adhered to said first wall panel before providing said first and second wall panels.

5. The method of claim 1 further including a step of filling said package with a product.

6. The method of claim 1 wherein said first and second wall panels are provided by folding a web of material.

7. The method of claim 7 wherein said zipper is positioned at a mouth of said first and second wall panels.

8. The method of claim 7 further including a step of filling said package with a product before adhering said second profile to said second wall panel.

9. The method of claim 1 wherein said zipper is positioned below and adjacent a mouth of said first and second wall panels.

10. The method of claims 9 further including a step of filling said package with a product before adhering said second profile to said second wall panel.

11. The method of claim 1 wherein said zipper is positioned at a bottom of said first and second wall panels.

12. The method of claim 11 further including a step of filling said package with a product after adhering said first profile to said first wall panel and after adhering said second profile to said second wall panel.

13. The method of claim 5 wherein said side seals are cut before filling said package with said product.

14. The method of claim 5 wherein said side seals are cut after filling said package with said product.

15. The method of claim 1 wherein said zipper has a tamper resistant element.

16. The method of claim 1 further including a step of mounting said slider onto said zipper.

17. The method of claim 16 wherein said slider is mounted onto said zipper after said first profile of said zipper is adhered to said first wall panel.

18. The method of claim 16 wherein said slider is mounted onto said zipper after said first profile of said zipper is adhered to said first wall panel and said second profile is adhered to said second wall panel.

19. A method of placing a product in recloseable packages, said method comprising:
 providing a first wall panel opposing a second wall panel;
 positioning a zipper at a predetermined orientation, said zipper including a first track with a first profile and a second track with a second profile, said first and second profiles being releasably engageable to each other;
 mounting a slider onto said zipper, said slider slidably mounted to said zipper for movement between a closed

10

position and an open position, said first and second profiles being engaged to each other while said slider is in said closed position, said first and second profiles being disengaged from each other in response to movement of said slider from said closed position to said open position;
 adhering said first profile of said zipper to said first wall panel;
 forming first and second spaced side seals in said first and second wall panels to define first and second sidewalls of said package;
 filling said package with a product; and
 adhering said second profile of said zipper to said second wall panel.

20. The method of claim 19 wherein said slider is mounted onto said zipper after said first profile of said zipper is adhered to said first wall panel.

21. The method of claim 19 wherein said slider is mounted onto said zipper after said first profile of said zipper is adhered to said first wall panel and said second profile is adhered to said second wall panel.

22. The method of claim 19 further including a step of feeding a zipper arrangement between said first and second wall panels before positioning said zipper, said zipper arrangement comprising a plurality of said zippers connected in line with each other.

23. The method of claim 22 wherein said zipper arrangement includes a plurality of sliders slidably mounted to said zipper.

24. The method of claim 19 further including a step of feeding a sheet of said zippers to between said first and second wall panels before positioning said zipper, said sheet of zippers comprising a plurality of said zippers releasably adhered to each other.

25. The method of claim 24 wherein each of said zippers includes a slider slidably mounted to said zipper.

26. The method of claim 19 wherein said zipper is positioned and said first profile of said zipper is adhered to said first wall panel before providing said first and second wall panels.

27. The method of claim 19 further including a step of cutting said side seals to separate adjacent packages.

28. The method of claim 19 wherein said first and second wall panels are provided by folding a web of material.

29. The method of claim 19 wherein said zipper is positioned at a mouth of said first and second wall panels.

30. The method of claim 29 wherein said package is filled with a product before adhering said second profile to said second wall panel.

31. The method of claim 19 wherein said zipper is positioned below and adjacent a mouth of said first and second wall panels.

32. The method of claim 31 wherein said package is filled with a product before adhering said second profile to said second wall panel.

33. The method of claim 19 wherein said zipper is positioned at a bottom of said first and second wall panels.

34. The method of claim 33 wherein said package is filled with a product after adhering said first profile to said first wall panel and after adhering said second profile to said second wall panel.

35. The method of claim 19 wherein said zipper has a tamper resistant element.

36. A method of manufacturing reclosable bags, said method comprising:
 providing a plurality of fastener segments connected to each other, each of said fastener segments including

11

first and second interlockable profiles, said first profile including a rib, said second profile including a groove for receiving said rib;
 mounting a slider to each of said fastener segments, said slider being adapted to open and close its respective fastener segment;
 providing a continuous web of plastic packaging material; after mounting said slider to each of said fastener segments, successively attaching said slider-carrying fastener segments to said continuous web;

12

forming said continuous web into the reclosable bags; and filling the reclosable bags with a product.

37. The method of claim 36, wherein said step of forming said continuous web into the reclosable bags includes folding said continuous web to form opposing walls of said reclosable bags and sealing said folded web to provide the reclosable bags with respective distinct interior compartments for receiving the product.

* * * * *